



FILETTATURA AMERICANA ASA (UNC)

TAV. A03

Designazione	Diametro esterno d	Passo n° fil ” p	Diametro medio dm	Diametro nocciolo dn
1 (.073)	1.864	64	1.597	1.366
2 (.086)	2.184	56	1.889	1.628
3 (.099)	2.514	48	2.171	1.864
4 (.112)	2.844	40	2.430	2.065
5 (.125)	3.175	40	2.763	2.395
6 (.138)	3.505	32	2.989	2.532
8 (.164)	4.165	32	3.649	3.192
10 (.190)	4.826	24	4.137	3.528
12 (.216)	5.486	24	4.798	4.188
1/4”	6.350	20	5.524	4.792
5/16”	7.937	18	7.020	6.205
3/8”	9.525	16	8.493	7.576
7/16”	11.112	14	9.933	8.887
1/2”	12.700	13	11.430	10.302
9/16”	14.287	12	12.913	11.691
5/8”	15.875	11	14.376	13.042
3/4”	19.050	10	17.339	15.933
7/8”	22.225	9	20.391	18.762
1”	25.400	8	23.337	21.503
1 1/4”	31.750	7	29.400	27.300

FILETTATURA AMERICANA ASA (UNF)

TAV. A04



Designazione	Diametro esterno d	Passo n° fil ” p	Diametro medio dm	Diametro nocciolo dn
0 (.060)	1.524	80	1.318	1.135
1 (.073)	1.854	72	1.625	1.422
2 (.086)	2.184	64	1.927	1.696
3 (.099)	2.514	56	2.219	1.958
4 (.112)	2.844	48	2.501	2.194
5 (.125)	3.175	44	2.799	2.466
6 (.138)	3.050	40	3.093	2.725
8 (.164)	4.165	36	3.708	3.299
10 (.190)	4.826	32	4.310	3.853
12 (.216)	5.486	28	4.897	4.373
1/4”	6.350	28	5.760	5.237
5/16”	7.937	24	7.249	6.639
3/8”	9.525	24	8.836	8.227
7/16”	11.112	20	10.287	9.555
1/2”	12.700	20	11.874	11.142
9/16”	14.287	18	13.370	12.555
5/8”	15.875	18	14.958	14.142
3/4”	19.050	16	18.018	17.101
7/8”	22.225	14	21.046	19.999